



Transferring sphere objects such as balls

• Tube 3 x 5 x 2000mm : 1 pc. • Tweezer (P-100): 1set • Stand : 1 pc.

• Needle 1 x 1.5 x 40 : 1 pc. • Pad 6 mm dia. : 1 pc. • Pad 4 mm dia. : 1 pc.

needle.

MH-100A is composed of:

 Vacuum Pump Unit Linicin Model LV-125A including 1 pc. of Micro Cupla MC04PH

The needle can be bent in accordance with applications. Please read the instruction booklet on how to bend the



Assembling precision parts



Moving tiny parts



Transferring uneven parts

electronic parts such as ICs and LSIs. Also precise micro parts such as watches, chemicals and other small parts.

Specifications of Vacuum Pump Unit Linicon Model LV-125A

Rated Voltage	115 V AC	230 V AC
Power Consumption	15 / 14 W	15 W
Rated Frequency	50 / 60 Hz	50 Hz
Maximum Vacuum	-33.3 kPa { -250 mmHg }, -33.3 mbar, -9.84 in.Hg	
Dimensions	135 mm(L) x 84 mm(W) x 146 mm (H) (5-5/16" x 3-11/32" x 5-3/4")	
Duty Cycle	Continuous	
Coil Insulation Class	B or its equivalent	E or its equivalent
Weight	1.5 kg (3.3 lbs.)	

★ Specifications and designs are subject to change at any time without notice.



Head Office

9-4, Nakaikegami 2-chome, Ohta-ku, Tokyo 146-8555 Japan NITTO KOHKI CO., LTD. Phone: +81-3-3755-1111 Fax: +81-3-3753-8791

E-mail: overseas@nitto-kohki.co.jp

URL: www.nitto-kohki.co.jp/e

DISTRIBUTED BY

